



3. The device according to claim 1, characterized in that in a recess (14) arranged coaxially with the center opening (10), the head part (9) has a sealed sliding ring (15) having axial play against spring force, said sliding ring slightly projecting beneath the head part (9) and jointly defining with a plane ring body (17) arranged fixed on the head part (9) and supporting a sealing ring (20), the plane of the blocking slide on the top and bottom sides in a watertight manner.

4. The device according to claim 3, characterized in that the ring body (17) is formed by any desired material and has in an annular groove (19) a sealing ring (20) defining the plane of the blocking slide.

5. The device according to claim 3, characterized in that the sliding ring (15) is supported in a watertight manner, for example on an O-ring made of springy-elastic material, arranged on a sealing ring (16) located in the coaxial recess (14), and displaceable by the sealing ring (16) in the direction of the ring body (17), said O-ring and the ring body (17) jointly keeping the plane of separation closed; and that the sliding ring (15) is movable by a component of the plugging force of the blocking slide (21) acting on the sliding ring (15) transversely to the direction of movement of the blocking slide (21), for releasing the plane of the blocking slide.



9. A device for holding the log transmitter of boat speedometers, comprising a sleeve body arranged in a fixed manner in a perforation in the hull of the boat and having an oblong center opening, in which the log transmitter provided with a fan wheel or the like as the pulse transmitter can be inserted and held in a watertight and detachable manner, characterized in that on the end facing away from the water, the sleeve body (32) supports in a watertight manner a head part (34) having a center opening (31') connected watertight with the oblong opening (39) of the sleeve body (32) and having the same shape and cross sectional size as the latter; that the oblong and the center openings (39; 31') jointly receive the log transmitter in a watertight manner; and that the oblong opening (39) and the center opening (31') can be blocked and released depending on the position of the log transmitter, by means of a blocking element (40) provided with a passage (38) and guided watertight and with swiveling mobility in the head part (34).

10. The device according to claim 9, characterized in that the head part (34) is connected with the sleeve body (32) in a detachable but fixed manner by means of a threaded ring (33) fixed on the head part.

11. The device according to claim 9, characterized in that the head part (34) comprises in a fixed manner a flange (37)

extending concentrically in relation to the oblong opening (39) and the center opening (31'), and a blocking element (40) with a passage (38), said blocking element resting watertight on the flange (37) and being capable of swiveling between two end positions, whereby said passage concentrically corresponding in the one end position of the blocking element with the oblong opening (39) and the center opening (31'), and in the other end position being movable into the closing position for closing the oblong opening (39) and the center opening (31').

12. The device according to claim 9, characterized in that on its top side, the flange (37) has a groove (36) for receiving an O-ring (36') serving as the sealing body; and that the blocking member (40) can be placed and guided against the O-ring (36') in a pressure-exerting and sealing manner by means of initial spring tension.

13. The device according to claim 12, characterized in that the initial tension of the spring can be expended by coil springs (41) supported on screw bolts (42, 42') fixed on the head part.

14. The device according to claim 13, characterized in that the blocking element (42) is pivot-mounted on the screw bolt (42) fixed on the head part, and receives and guides in a

slide groove the other screw bolt (42') fixed on the head part.

15. The device according to claim 11, characterized in that the blocking element (40) is formed by a plate-shaped, molded component having a sleeve-like attachment (40'') arranged on the side facing away from the sleeve body (32).